



Specification

D	Magnification	-0.02X	-0.05X	-0.12X
	Working Distance	1750±5	700±5	298±5
	Image Distance	/	/	/
	Conjugate Distance	1821±9	772±9	372±9
	Flange Focal Distance			
E	Max Image	ø32		
	F/#	2.8~16		
	EFL	35		
	FOV	43°		
F	ENP Diameter	12.4		
	Distortion	<0.1%		
	Structure	6G		
	Image Quality			
	Axis	ø16	ø21	ø32
	125lp/mm	100lp/mm	80lp/mm	

倍率	共轭距	工作距	Φ14视场	Φ28视场	Φ32视场
0.02x	1821	1750	700.0	1400.0	1600.0
0.03x	1241	1170	466.7	933.3	1066.7
0.04x	952	880	350.0	700.0	800.0
0.05x	772	700	280.0	560.0	640.0
0.06x	657	585	233.3	466.7	533.3
0.07x	578	505	200.0	400.0	457.1
0.08x	516	443	175.0	350.0	400.0
0.09x	467	394	155.6	311.1	355.6
0.10x	429	355	140.0	280.0	320.0
0.11x	397	323	127.3	254.5	290.9
0.12x	372	298	116.7	233.3	266.7

							图面名称			镜头规格书		
							机种名称			LS3528H0.05A		
						绘图			材料	/	版本	V0
						校对			表面处理	/	比例	1:1
						审核			单位	mm	页次	1/1
标记	处数	变更内容/原因		担当	变更日期	批准			视图			A4