



Specification

Magnification	-0.02X	-0.05X	-0.075X
Working Distance	3050±5	1240±5	834±5
Image Distance	/	/	/
Conjugate Distance	3167.8±9	1359.6±9	955.1±9
Flange Focal Distance			
Max Image	ø62		
F/#	4.5~22		
EFL	60		
FOV	50.1°		
ENP Diameter	13.3		
Distortion	<0.05%		
Structure	12G		
Image Quality			
Axis	ø28	ø43	ø56
250lp/mm	200lp/mm	160lp/mm	160lp/mm

倍率	共轭距	工作距	ø43.27视场	ø57视场	ø60视场
0.02x	3167.8	3050	2163.5	2850.0	3000.0
0.025x	2568.1	2450	1730.8	2280.0	2400.0
0.03x	2163.4	2045	1442.3	1900.0	2000.0
0.035x	1878.7	1760	1236.3	1628.6	1714.3
0.04x	1659	1540	1081.8	1425.0	1500.0
0.045x	1489.3	1370	961.6	1266.7	1333.3
0.05x	1359.6	1240	865.4	1140.0	1200.0
0.055x	1249.9	1130	786.7	1036.4	1090.9
0.06x	1150.3	1030	721.2	950.0	1000.0
0.065x	1075.6	955	665.7	876.9	923.1
0.07x	1010.9	890	618.1	814.3	857.1
0.075x	955.1	834	576.9	760.0	800.0

							图面名称			镜头规格书		
							机种名称			LS1660H0.05A		
						绘图			材料	/	版本	V0
									表面处理	/	比例	1:1
						校对			单位	mm	页次	1/1
									视图			A4
标记	处数	变更内容/原因			担当	变更日期	批准					

1

2

3

4

5

6

7